

DATASHEET
SFX-RT5x



► Highlights

- OleumTech® field-proven technology running on the global Sigfox Low-Power Wide Area (LPWA) network
- SFX-RT51 available with a 2" to 18" RTD sensor
- SFX-RT52 supports third-party RTD sensors
- High accuracy of $\pm 0.06\%$ @ 0 °C (RT51)
- Powered by a replaceable internal battery pack
- Battery life up to 8 years¹
- NEMA 4X / IP66 / -40 °C to 70 °C
- Industrially-hardened self-contained design
- A global solution – Zones RCZ1/2/4
- Remote antenna-ready option available
- Intrinsically Safe, Class I, Div 1 (Zone 0) certified



OleumTech Sigfox Ready Transmitters



Sigfox Base Stations



Sigfox Cloud™



Third-Party Customer IT

► Unlock the True Potential of IoT (Internet of Things)

Easiest Way to Get Data in the Cloud

The OleumTech® Sigfox Ready SFX-RT51 and SFX-RT52 Wireless RTD Temperature Transmitters are designed for deployment anywhere in the world that Sigfox has network coverage. By leveraging the Sigfox Low Power Wide Area (LPWA) network, you can take advantage of the world's leading Internet of Things (IoT) connectivity service, offering a software-based communications solution where all the network and computing complexity is managed in the Sigfox CLOUD™.

Designed for Use in Hazardous Locations

The SFX-RT51 and SFX-RT52 are certified for use in Class I, Division 1 (Zone 0) hazardous locations. They are intrinsically safe, designed not to cause a spark, and can be serviced without being removed from a process. The SFX-RT51 is a direct mount type that is available with a 4-wire Platinum 100 ohm Class A RTD sensor. The SFX-RT52 is designed to support a third-party RTD sensor: 2, 3, or 4-wire type.

Inherently Secure

The Sigfox Ready Transmitters take advantage of the built-in firewall since they are not directly connected to the internet and do not use Internet Protocol. Layered on top of this secure foundation, OleumTech provisions each device with a unique symmetrical authentication key. Each message sent by the transmitter contains a cryptographic token that is computed based on this authentication key and verified by each Sigfox Base Station.

Extremely Reliable

The Sigfox architecture is based on multiple base stations receiving each broadcasted and repeated message, building redundancy into the solution. Data Integrity, availability, and confidentiality are at the core of the offering.

Technical Specifications

HARDWARE FEATURES

| | |
|----------------------|--|
| Device Functionality | · Class I, Division 1 (Zone 0) IoT Wireless Transmitter Supporting RTD Sensors |
| Embedded Controller | · Ultra-Low Power RISC Microcontroller with Internal FLASH (Field Upgradeable) |
| Configuration | · OleumTech Sigfox Ready Transmitter Configuration Tool via RS232 Serial |
| ADC Resolution | · 24-bit High Resolution Delta-Sigma ADC |
| Reportable Values | · Temperature Level / Battery Voltage |
| Device Diagnostics | · Health Tag: Battery Voltage |

RTD TEMPERATURE SENSOR

| | |
|-------------------------|--|
| RTD Element | · Platinum 100 Ohm, Class A (RT51) |
| Temperature Coefficient | · 0.00385 (RT51) |
| Probe Lengths | · 2" to 18" / 30.5 to 45.5 cm in 1" / 25 mm Increments |
| Temperature Range | · RT51: -67 °F to 500 °F (-55 °C to 260 °C); RT52: Temperature Range Depends on Sensor |
| Accuracy | · RT51: ±0.06% @ 0 °C; RT52: Accuracy Depends on Sensor |
| Materials | · Probe Cover - Silver Coated Copper / Probe Insulation - PTFE |

WIRELESS COMMUNICATIONS

| | |
|--------------------------------------|--|
| Sigfox Radio Zones/Regions Supported | · RCZ1: Europe, Oman, South Africa Certificate ID: P_009D_53CD_01 |
| | · RCZ2: USA, Canada, Mexico, Brazil Certificate ID: P_009D_D78E_01 |
| | · RCZ4: Australia, New Zealand, Colombia, Peru, Singapore Certificate ID: P_009D_D78E_01 |
| | · Certificate ID: P_009D_D78E_01 |
| Wirelessly Connects To | · Sigfox Base Stations |
| Data Reporting Modes | · Interval Only |

CERTIFICATIONS & COMPLIANCE

| | |
|---------|---|
| EMC/EMI | · FCC Part 15 (USA), IC ICES-003 (Canada), ACMA (Australia) |
| Safety | · Class I, Division 1, Groups A, B, C, D T3C; Ex ia IIC T3 |
| | · Class I, Zone 0; AEx ia IIC T3 |
| | · ATEX: Sira 13ATEX2142X; Ex ia IIC T3 Ga; II 1 G |
| | · IECEx: SIR 13.0054X; Ex ia IIC T3 Ga |

MECHANICAL SPECIFICATIONS

| | |
|---------------------------|--|
| Dimensions, RT51 | · 5" (W) x 7.6" (H) x 4.4" (D) / 127 mm (W) x 193 mm (H) x 112 mm (D) - Excludes RTD Length |
| Dimensions, RT52 | · 5" (W) x 12.3" (H) x 6.4" (D) / 127 mm (W) x 313 mm (H) x 163 mm (D) - Excludes RTD Length |
| Package Dimensions | · 10.25" (W) x 14" (H) x 6.5" (D) / 260mm (W) x 356mm (H) x 165mm (D) |
| Weight, RT1 | · Net: 2.75 lbs / 1.4 kg; Gross: 4.75 lbs / 2.2 kg |
| Weight, RT2 | · Net: 4.75 lbs / 2.1 kg; Gross: 6.5 lbs / 2.9 kg |
| Connection Fitting | · RT1: 1/2" NPT Male; RT2: 3/4" NPT Female |
| Enclosure Casing Material | · Aluminum, NEMA 4X, IP66 |
| Mounting Holes | · 4x M5 Female Threads; Horizontal Spacing: 2.76" (70 mm); Vertical Spacing: 3.70" (94 mm) |

ELECTRICAL SPECIFICATIONS



| | |
|-----------------------|---|
| Power Source | · SX1000-BP3, Internal 3.6 Vdc Lithium Battery |
| Internal Battery Life | · Up to 8 Years, Based on User Defined Reporting Intervals ¹ |

GENERAL SPECIFICATIONS

| | |
|----------------------|--|
| Operating Conditions | · Ambient Temperature (Class I, Division 1 / Zone 0): -40 °F to 158 °F (-40 °C to 70 °C) |
| | · Ambient Temperature (ATEX/IECEx): -22 °F to 158 °F (-30 °C to 70 °C) |
| | · Humidity: 0 to 99 %, Non-Condensing |
| Warranty | · 2-Year Parts and Labor |
| Country of Origin | · USA |

ORDERING INFORMATION

| | |
|---|---|
| Model Number(s) | · RCZ1: SFX-RCZ1-RT51 (Direct Mount, Includes RTD) SFX-RCZ1-RT52 (Multi-Vendor) |
| | · RCZ2: SFX-RCZ2-RT51 (Direct Mount, Includes RTD) SFX-RCZ2-RT52 (Multi-Vendor) |
| | · RCZ4: SFX-RCZ4-RT51 (Direct Mount, Includes RTD) SFX-RCZ4-RT52 (Multi-Vendor) |
| | · RCZ1: SFX-RCZ1-RT51-P (Direct Mount, Includes RTD) SFX-RCZ1-RT52-P (Multi-Vendor) |
| Model Number(s) for Remote Antenna-Ready Option | · RCZ2: SFX-RCZ2-RT51-P (Direct Mount, Includes RTD) SFX-RCZ2-RT52-P (Multi-Vendor) |
| | · RCZ4: SFX-RCZ4-RT51-P (Direct Mount, Includes RTD) SFX-RCZ4-RT52-P (Multi-Vendor) |
| | · RCZ1: SFX-RCZ1-RT51-P (Direct Mount, Includes RTD) SFX-RCZ1-RT52-P (Multi-Vendor) |
| Battery Model Number | · Use Only SX1000-BP3, 3.6 V Lithium Battery Pack |
| Configuration Cable | · SX1000-CC2, 20-ft All-in-One Configuration Cable |



¹ Ambient temperature and 140 transmissions per day were used to calculate battery life. The data only applies to a new battery part number SX1000-BP3. Actual battery life may vary depending on environmental factors, application, and usage. Use data shown above only as general point of reference.

©2018 OleumTech Corporation. All rights reserved. OleumTech is a registered trademarks of OleumTech Corporation in the United States. All other trademarks and trade names are the property of their respective holders. Specifications, design, and product descriptions subject to change without notice. This device contains proprietary intellectual property protected by US Patent #6967589. Document ID: 67-4090-001_D

